

Snug Mat FME 150Watt/m²

Description

The Snug FME mat is an easy installation solution, designed to produce a gentle even heat, and is ideal for use under carpet and wood. The mat is laid on top of our 3mm thick closed cell insulation. These two combined will raise your floor by only 4mm, making it the thinnest mat on the market for this type of installation. If you are planning on using a wood finish, the wood must be laid as a floating floor. Heater mats are available from 1-12m² and are rated at 150 Watts/metre. When being installed under carpet we recommend that both the carpet and the underlay do not exceed a rating of 2 tog, and that an RCD is fitted by the electrical installer.



- Available from 1 to 12m²
- Available in 230V
- Double insulated
- Designed to be laid on concrete, marine ply or construction boards with tiles, stone
- Ideal for comfort heating in kitchens, bathrooms and wet rooms
- 4m cold tail
- Designed to be laid under ceramic tiles, slate, terracotta, marble, stone and limestone

Specification

Output: 150W/m

Voltage: 230V

Cable Thickness: 1.18-1.62mm

Max. temp output: +80°C

Min. temp output: -10°C

Min storage temp: -20°C

Min installation temp: -10°C

Cold lead cross section:

Until 4m²: 2 x 0.5mm²

5m² to 9m²: 2 x 0.75mm²

10m²: 2 x 1.0mm²

