



SNUG CABLE 10

10CABLE

Snug Cable 10

OVERVIEW

The Snug Cable is designed for awkward or small areas where a mat cannot be used.

Manufactured in a wide range of ready-made sizes and with the supply lead wire at one end only. It is supplied on a roll for quick and easy installation.

This design offers maximum flexibility to the installer; is easy to plan and lay; and is suitable for large or small areas.

KEY FEATURES

- Designed for areas too small for matting.
- Ideal as an economical single heat source
- One simple connection cable
- Supplied with fixing tape
- One of the thinnest on the market at just 2mm
- Triple insulated
- 3m Cold tail
- FEP (Fluoropolymer) cable jacket
- Available from 10m to 150m
- Lifetime cable warranty



SNUG CABLE 10

SPECIFICATIONS

Output	10W/m ²
Thickness	2mm Wire
Voltage	230V
Max. Temperature Output	+80°C
Warranty	Lifetime cable warranty
Protection Class	1 RCD
Connection	One side connection
Colour	Yellow or Pink
Last Insulation	PVC

CABLE LOADINGS

PART NO:	CABLE LENGTH (M)	Floor Area (M ²)				TOTAL WATTS	TOTAL AMPS	TOTAL CABLE RESISTANCE (OHMS)
		100w/m ² (100mm spacings)	120w/m ² (82mm spacings)	160w/m ² (62mm spacings)	200w/m ² (50mm spacings)			
10 Cable 10	10	1	0.83	0.62	0.5	100	0.44A	480-556Ω
10 Cable 20	20	2	1.67	1.25	1	200	0.9A	240-290Ω
10 Cable 30	30	3	2.5	1.87	1.5	300	1.30A	160-195Ω
10 Cable 40	40	4	3.34	2.5	2	400	1.7A	120-142Ω
10 Cable 60	60	6	5	3.75	3	600	2.6A	80-90Ω
10 Cable 80	80	8	6.67	5	4	800	3.5A	61-68Ω
10 Cable 100	100	10	8.34	6.25	5	1000	4.4A	49-55Ω
10 Cable 120	120	12	10	7.5	6	1200	5.2A	40-46Ω
10 Cable 150	150	15	12.5	9.37	7.5	1500	6.5A	32-37Ω